

VAS 741 075 Tire Changer

Powerful and operator-friendly

NEW



TCX70-21UVE shown

Specifications

Power requirements	230V, 1ph, 50/60HZ
Air supply requirements	8-12 bar (115-175 psi)
Mount / demount tool	Leverless head
Clamping type	Center with Quick Clamp
Bead loosening type	Upper / lower roller
Match-mounting capable	Yes
Rim diameter range	12-30 in. (305-762 mm)
Maximum...	
Tire diameter	45 in. (1143 mm)
Wheel width	15 in. (381 mm)
Drive	7 / 17 rpm clockwise, 7 rpm counter-clockwise
Torque	880 Nm (650 ft-lbs.)
Dimensions	
Height	2135 mm (84 in.)
Width	1425 mm (56 in.)
Depth	1675 mm (66 in.)

Some dimensions, capacities and specifications may vary depending on tire and wheel configurations.

Model

TCX70-21UVE 230V, 1ph, 50/60HZ

Standard equipment

- ✓ Large 145mm metal cone (RP11-5-103627)
- ✓ Standard 120mm metal cone protectors (2 pieces) (RP11-4-103232A)
- ✓ Small 58mm cone (RP11-462414B)
- ✓ Small 74mm cone (RP11-4-118295A)
- ✓ Cone spacer (RP11-5-103627)
- ✓ Valve core remover (RP11-2020689)
- ✓ Bead starting tool (RP11-4-405496A)
- ✓ Bead-pressing clamp (MPR) (RP11-801262417)
- ✓ Wheel lift (RP11-8-11100415)
- ✓ Paste & brush

Because of continuing technological advancements, specifications, models and options are subject to change without notice.

1118AH

Copyright © 2018, Hunter Engineering Company



TCX70-21UVE

Optional equipment



Blast inflator **RP11-8-11100416**

Directs large blast of compressed air exactly where needed to seat the bead.



Reverse rim flange kit **RP11-8-11100039**

Ideal for plastic clad wheels or reverse wheels where maximum protection is needed.



Clamp adaptor **RP11-8-11100417**

Adds clamping capability for truck wheels with large center holes. Adds clamping height for high offset wide wheels.

